



_Technical data		2 GROUP	3 GROUP
voltage	٧	220-240 1N 50/60Hz*	
required amperage	A	20	32
power input	kW	4.5	6.9
steam boiler capacity	lt	7	10
steam boiler element	kW	3.5	5.5
pump power	kW	0.15 Std / 0.2 Pro	0.15 Std / 0.2 Pro
net weight	kg	85	95

^{*3} phase electrical conversion available at additional cost.

CONTACT US

info@sanremomachines.com.au sanremomachines.com.au



Features



DIGITAL SHOT TIMER

Allows you to accurately and reliably time coffee extraction



UP TO 7 PROGRAMMABLE DOSES

Choose between 5 or 7 programmable



ECO MODE

Smart energy management



AISI 316L STAINLESS STEEL "COOL TOUCH" STEAM WANDS

Anti-burning feature even in conditions of prolonged use, fitted with milk resistant high-performance steam terminals



AISI 316L STAINLESS STEEL BOILER

Exclusive Sanremo design ensures exceptional thermal stability and maximum resistance to oxidation and limescale



ADJUSTABLE BREW TEMPERATURE ACROSS ALL GROUP HEADS

Digitally adjust the brew temperature for all group heads



DIGITALLY PROGRAMMABLE BOILER TEMP.

Digitally adjust the boiler temperature to increase or decrease steam pressure



AUTOMATIC CLEANING CYCLE

Process for coffee groups cleaning

_D8 Pro Features

THE ABOVE PLUS:



BARISTA LIGHTING

Allows efficient working in any condition of environmental lighting



ECO MODE PRO

Insulation and smart energy management



MIXED INFUSION HOT WATER TAP FOR TEA

Instantaneous mixing of fresh water and steam boiler



INSULATED BOILER

Steam boiler insulation to improve performance and recovery



COLOUR LCDs

Multi-coloured LCDs per group, to show mls, temperature and shot time



HIGH PERFORMANCE PUMP 200L/H

Pressure stability in situations of prolonged use of multiple groups even in high volume venues



ADJUSTABLE BREW TEMPERATURE FOR EACH GROUP HEAD

Digitally adjust the brew temperature independently for each group head

_Optional Features




IOT CONNECTIVITY

Wifi board to give live coffee quality telemetry and service updates from the cloud



SANREMO


_Versions and Dimensions



Τ	2 GROUP	3 GROUP	
19.5	2 steam taps	2 steam taps	
inches 496 mm	1 water tap	1 water tap	
	1 one-cup portafilter	1 one-cup portafilter	
	2 two-cup portafilters	3 two-cup portafilters	

Dispensing 2 coffees Dispensing 1 long coffee Dispensing 1 long coffee Mini - Display D8 "shot timer" Extra dose 1 Manual dose and/or purge/flush


2 GROUP



— 21.8 inches / 554mm —



3 GROUP



40.8 inches / 1037mm

D8 PRO DISPLAY FUNCTIONS

PUSH-BUTTON PANEL

OF D8 AND D8 PRO

WiFi connection

Warning - indicates maintenance required

User menu navigation
Cup heating plate ON

Pressure display
Group washing

Eco Pro mode Boiler level OK Alarm

Technical menu navigation - service Water dispensing

Temperature display

Shot timer

Dispensed coffee quantity display Hourly programming

_Colours





All images are subject to illustrative purpose. The manufacturer reserves the right to modify without prior notice the technical characteristics indicated above.

