

Pratic Avant Xtra Fact Sheet





Standard Features

- Single boiler, heat exchange system
- Preinfusion technology
- Turn style steam knobs
- Raised groups (up to 20oz cup) & barista downlights
- (SAE) 4 programable, volumetric dosing touch pads
- (AEP) 1 manual dosing button per group
- Manual pressure stat
- Automatic (SAE) and Semiautomatic (AEP) versions
- Temperature stabilized groups (thermosiphoned)

Color Options

- Black/Stainless Steel
- White/Stainless Steel





	SAE/AEP 1 🔘	SAE/AEP 2 🔵	SAE 3
Total Wattage	2330 watt	4,800 watt	5,350 watt
Heating Element	2,000	4,400	5,000 watt
Boiler	5.2 ltr	9 ltr	14.7 ltr
Net Weight	130 lbs	160 lbs	190 lbs
Approx Ship Weight	210 lbs	240 lbs	270 lbs
Measurements W x D x H	22" x 22" x 21.5"	30.5" x 22" x 21.5"	40" x 22" x 21.5"
Power	120 volt/ 19.4 amps	220 volt/21.4 amps	220 volt/ 23.2 amps
W. L. D. J. L. L.	NEMA LS-30P	Nema L6-30	Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting
- water hardness must be between 3-5 grains per gallon or 50-85 ppm
- water softener and/or filter must be installed if it exceeds the limits
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI / 5 BAR

Drain Requirements

-Open gravity drain of minimum 1.25 inches within 4 feet of the machine

